

ELECTRIC FORKLIFT
TASK A-Series

SALES BROCHURE



FORKLIFT **SALES, SERVICE & RENTALS**



TASKFORKLIFTS.COM.AU



SALES@TASKAUSTRALIA.COM.AU



CALL US: 1300 13 2002

+ TASK A-SERIES

3-WHEEL ELECTRIC FORKLIFT

The TASK A-Series is designed for optimal operator comfort, safety and efficiency. The new TASK A-Series is available with a 4.8m, 3 stage mast on allowing operators to use the A-Series forklift inside a container if required.

As a standard feature the A-Series 3-wheel electric forklifts also come with Side-shift. The smooth handling regardless of whether the forklift is loaded, traveling or lifting makes the A-Series an ideal choice for the discerning operator needing a highly maneuverable forklift.



3.3m - 6m
Lift Height



1.5T - 4T
Capacity



Container
Mast Option



Side-Shift as
Standard



Low Carbon
Footprint



Battery
Electric Forklift



TASK A-SERIES

INDUSTRIES.



General
Warehousing



Factory



General
Engineering



Logistics &
Distribution



Carpets &
Flooring



Supermarkets



Retail



Construction



Wineries &
Breweries

3-WHEEL
ELECTRIC

EMAIL: SALES@TASKAUSTRALIA.COM.AU

WEB: TASKFORKLIFTS.COM.AU

CALL US: 1300 13 2002

• ADELAIDE • SYDNEY • MELBOURNE • BRISBANE • SINGAPORE • SHANGHAI • DALLAS •

+ TASKA-SERIES

3-WHEEL ELECTRIC FORKLIFT



Energy Efficient
LED Lights



Operator
Detection System



Reverse
Assist Grip



Overhead
Guard Protection



Wide-View
Mast.



Manufacturers
Warranty

STANDARD FEATURES.

- 1500kg - 4000kg Lifting Capacity
- 3.3m - 6.0m Lifting Height
- Two stage and three stage mast configurations
- Full Free Lift Available with 3-stage mast configuration
- 508ah Industrial Lead Acid Battery
- Intelligent External (Three-Phase) Charger
- Tilting Mast as standard
- Side-shift function as standard
- Electric Power Steering
- 3-Wheel and 4-Wheel Configurations
- Excellent Leg Room in the operator compartment
- Intuitive Dash Display
- Wide mast for increase visibility
- Can be to adjusted to meet environmental requirements
- Built to Australian Standards

OPTIONAL EXTRAS.



Container
Mast.



Integrated Side-shift
Fork Positioner.



Digital Weight
Gauge.



Worker
Accessories.



Rotator & Clamp
Attachments.



Optional
Camera.



TASKA-SERIES

3-WHEEL
ELECTRIC

EMAIL: SALES@TASKAUSTRALIA.COM.AU

WEB: TASKFORKLIFTS.COM.AU

CALL US: 1300 13 2002

• ADELAIDE • SYDNEY • MELBOURNE • BRISBANE • SINGAPORE • SHANGHAI • DALLAS •

+ TASKA-SERIES

3-WHEEL ELECTRIC FORKLIFT

TASKA-SERIES

4-WHEEL
ELECTRIC

		TASK A-Series 3-Wheel Electric Forklift		
Load capacity/rated load	kg	1500	1800	2000
Load centre distance	mm	500	500	500
Wheelbase	mm	1250	1358	1466
Service Weight	kg	2980	3240	3470
Tyres		Solid	Solid	Solid
Tyre size, front		18x7 - 8	18x7 - 8	18x7 - 8
Tyre size, rear		15 x4.5 - 8	15 x4.5 - 8	15 x4.5 - 8
Wheels, number front rear (x = driven wheels)		2x/2	2x/2	2x/2
Seat height/stand height	mm	1000	1000	1000
Overall length	mm	2710	2823	2930
Length to face of forks	mm	1790	1903	2010
Overall width	mm	1086	1086	1120
Fork dimensions	mm	40/122/1070	40/122/1070	40/122/1070
Fork-carriage width	mm	1000	1000	1000
Ground clearance, centre of wheelbase	mm	110	110	110
Turning radius	mm	1452	1555	1660
Travel speed, laden/unladen	kph	16/16	16/16	15/15
Lift speed, laden /unladen	m/s	0.390/0.470	0.370/0.450	0.350/0.450
Lowering speed, laden/unladen	m/s	0.460/0.440	0.460/0.420	0.470/0.420
Max. gradeability, laden/unladen	%	20/20	18/20	15/18
Service brake		Hydraulic	Hydraulic	Hydraulic
Parking brake		Mechanical	Mechanical	Mechanical
Battery voltage	V/Ah	48/400	48/500	48/600
Battery weight	kgs	700	920	1000
Battery dimensions	mm	830•522•627	830•630•627	830•738•627
Drive Controller Manufacturer		CURTIS	CURTIS	CURTIS
Operating pressure for attachments	bar	150	150	150
Oil volume for attachments	l/min	35	35	35
Hydraulic Tank - capacity (drain & refill)	liter	24	26	29

		TASK A-Series 3-Wheel Electric Forklift // Mast Options	
Lift Height	mm	4800	6000
Collapsed height	mm	2175	2625
Mast configuration		Three Stage // Full Free Lift	Three Stage // Full Free Lift
Tilt (Forward / Reverse)	Deg.	3.5° / 5°	3.5° / 5°