

ELECTRIC FORKLIFT
TASK A-Series

SALES BROCHURE



FORKLIFT **SALES, SERVICE & RENTALS**



TASKFORKLIFTS.COM.AU



SALES@TASKAUSTRALIA.COM.AU



CALL US: 1300 13 2002

+ TASK A-SERIES 4-WHEEL ELECTRIC FORKLIFT

NEXT GEN POWER.

The TASK® A-Series 4-Wheel is our newest generation of battery electric counterbalance forklifts. Designed around operator comfort, the new A-Series has a smaller steering wheel, adjustable suspension seat and wide view mast to enhance safety and efficiency. The new TASK® A-Series is available with a 4.5m, 3 stage mast on allowing operators to use the A-Series forklift inside a container if required.

The multi-functional Digital display by Curtis® provides running hours, battery power, and self diagnosis functions. As a standard feature the A-Series 4-wheel electric counterbalance forklifts also come with integrated side-shift. The smooth handling regardless of whether the forklift is loaded, traveling or lifting makes the TASK® A-Series an ideal choice for operators needing a highly maneuverable forklift.



3.3m - 6m
Lift Height



2.0T - 5.0T
Capacity



Full Free-Lift
Container Mast



Side-Shift as
Standard



Low Carbon
Footprint



Battery
Electric Forklift

TASK A-SERIES

INDUSTRIES.



General
Warehousing



Factory



General
Engineering



Logistics &
Distribution



Carpets &
Flooring



Retail



Construction



Wineries &
Breweries



4-WHEEL
ELECTRIC

EMAIL: SALES@TASKAUSTRALIA.COM.AU

WEB: TASKFORKLIFTS.COM.AU

CALL US: 1300 13 2002

• ADELAIDE • SYDNEY • MELBOURNE • BRISBANE • SINGAPORE • SHANGHAI • DALLAS •

+ TASKA-SERIES

4-WHEEL ELECTRIC FORKLIFT



Energy Efficient
LED Lights

ODS

Operator
Detection System



Reverse
Assist Grip



Overhead
Guard Protection



Wide-View
Mast.

1year
Unlimited Hours
Warranty

Manufacturers
Warranty

STANDARD FEATURES.

- 2000kg - 5000kg Lifting Capacity
- 3.3m - 6.0m Lifting Height
- Two stage and three stage mast configurations
- Full Free Lift Available with 3-stage mast configuration
- Industrial Lead Acid Battery
- Intelligent External (Three-Phase) Charger
- Tilting Mast as standard
- Side-shift function as standard
- Electric Power Steering
- 4-Wheel Configuration
- Excellent Leg Room in the operator compartment
- Intuitive Digital Dash Display by Curtis®
- Wide mast for increase visibility
- Can be to adjusted to meet environmental requirements
- Tested to Australian Standards

OPTIONAL EXTRAS.



Container
Mast.



Integrated Side-shift
Fork Positioner.



Digital Weight
Gauge.



Worker
Accessories.



Rotator & Clamp
Attachments.



Optional
Camera.



TASKA-SERIES

4-WHEEL
ELECTRIC

EMAIL: SALES@TASKAUSTRALIA.COM.AU

WEB: TASKFORKLIFTS.COM.AU

CALL US: 1300 13 2002

• ADELAIDE • SYDNEY • MELBOURNE • BRISBANE • SINGAPORE • SHANGHAI • DALLAS •

+ TASKA-SERIES

4-WHEEL ELECTRIC FORKLIFT

TASKA-SERIES

		A-Series 2.5T			A-Series 3.5T		
Load Capacity	(kg)	2500			3500		
Load Centre	(mm)	500			500		
Mast Height	(mm)	Triplex			Triplex		
Lift Height	(mm)	4500	5000	6000	4500	5000	6000
Collapsed Height	(mm)	2061	2411	2611	2211	2461	2911
Retained Capacity (at max. height)	(kg)	2050	1650	1000	3400	3300	2200
Tyre		Solid Tyre			Solid Tyre		
Tyre size, Front		23x9-10-18PR			23x10-12		
Tyre size, Rear		18x7-8-14PR			200/50-10		
Wheels, Number front / rear		2x2			2x2		
Tilt of mast Forward/Backward	(deg.)	6/ 10			6/ 10		
Height of overhead guard	(mm)	2160			2160		
Overall Length	(mm)	3417			3647		
Length to Face of Forks	(mm)	2347			2577		
Overall Width	(mm)	1180			1260		
Fork Dimensions	(mm)	40*122*1070			50*125*1070		
Fork Carriage Width	(mm)	1008			1082		
Ground clearance, centre of wheelbase	(mm)	120			125		
Turning radius	(mm)	2055			2230		
Travel speed, laden/unladen	(km/h)	16.5/17.5			14/15		
Lift speed, laden/unladen	(m/s)	0.34/0.60			0.30/0.45		
Lowering speed, laden/unladen	(m/s)	0.45/0.50			0.47/0.47		
Service brake		Hydraulic			Hydraulic		
Parking brake		Mechanical			Mechanical		
Battery voltage, nominal capacity K5	(V/ Ah)	48/ 600			80/ 460		
Drive Controller		Curtis			Curtis		
Operating pressure for attachments	(bar)	160			160		
Oil volume for attachments	(l/min)	65			65		

4-WHEEL
ELECTRIC

+ TASKA-SERIES

4-WHEEL ELECTRIC FORKLIFT

TASKA-SERIES

		A-Series 4.0T			A-Series 5.0T		
Load Capacity	(kg)	4000			5000		
Load Centre	(mm)	500			600		
Mast Height	(mm)	Triplex			Triplex		
Lift Height	(mm)	4250	4500	6000	4300	4500	6000
Collapsed Height	(mm)	2180	2250	2825	2250	2315	2975
Retained Capacity (at max. height)	(kg)	4000	4000	3710	4990	4990	4610
Tyre		Solid Tyre			Solid Tyre		
Tyre size, Front		250-15			28x12.5-15		
Tyre size, Rear		21x8-9			23x9-10		
Wheels, Number front / rear		2x2			2x2		
Tilt of mast Forward/Backward	(deg.)	5° / 6°			5° / 6°		
Height of overhead guard	(mm)	2360			2360		
Overall Length	(mm)	3980			4275		
Length to Face of Forks	(mm)	2910			3075		
Overall Width	(mm)	1385			1494		
Fork Dimensions	(mm)	50*150*1070			60*150*1200		
Fork Carriage Width	(mm)	1200			1200		
Ground clearance, centre of wheelbase	(mm)	152			152		
Turning radius	(mm)	2540			2680		
Travel speed, laden/unladen	(km/h)	16.5/16.5			15.5/16.5		
Lift speed, laden/unladen	(m/s)	0.33/0.475			0.31/0.475		
Lowering speed, laden/unladen	(m/s)	0.48/0.43			0.5/0.4		
Service brake		Hydraulic			Hydraulic		
Parking brake		Mechanical			Mechanical		
Battery voltage, nominal capacity K5	(V/ Ah)	80/ 600			80/ 700		
Drive Controller		Curtis			Curtis		
Operating pressure for attachments	(bar)	185			200		
Oil volume for attachments	(l/min)	76			76		

4-WHEEL
ELECTRIC