# STRADDLE STACKER TASKCONDA

SALES BROCHURE



FORKLIFT SALES, SERVICE & RENTALS









## + TASKCONDA® STRADDLE STACKER



1500kg Capacity.



Up to 4.5m Lift Height.



Power Steering.



No License Required.

Integrated Tilting Carriage.

Integrated Side-shift.

### COMPACT & EASY TO USE.

The CONDA® pedestrian stacker is designed for indoor use and perfect for a wide variety of applications such as workshops, warehouses and storage centers.

Operators find the CONDA® pedestrian stacker a compact, simple and easy to use. The electronic power steering allows users to work in very narrow aisle spacings; and the optional three stage "full free lift" mast is an ideal solution for users working within tight height restrictions.

The unit comes as standard with a tilting carriage and sideshift allowing operators to maneuverer pallets and materials safer, and more efficiently.





### **CURTIS® CONTROLLED.**

The Curtis® Programmable Control System with Multi-mode allows infinite control of all machine functions.



Authorised TASK® support technicians are able adjust and optimise settings to meet environmental requirements or different operator skill levels.

**STRADDLE STACKER** 

**ASKCONDA** 

**EMAIL:** SALES@TASKAUSTRALIA.COM.AU

WEB: TASKFORKLIFTS.COM.AU

**CALL US:** 1300 13 2002



# + TASKCONDA® STRADDLE STACKER



Large Industrial **Battery** 

**ASKCONDA** 

**STRADDLE STACKER** 



Single-Point **Battery Filling** 



240v Internal Charger



**Latest Curtis** Controller



TASK Genuine Parts Availablilty



Manufacturers Warranty

#### STANDARD FEATURES.

- 1500kg Capacity
- 2.5m 4.5m Lifting Height
- Two stage and Three Stage Mast Configurations
- Full Free Lift Available
- Intelligent AC Drive Motor
- Tilting Carriage as standard
- Integrated Side-Shift as standard
- Responsive Electric Power Steering

- American Designed Curtis Controller
- TASK Transmission
- Single Point Battery Filling System Included
- Super Quiet Drive Motor
- Built and Tested to Exceed Australian Standards
- 1-year, Unlimited Hours Warranty
- Emergency Stop Button for Increased Safety



#### **OPTIONAL EXTRAS.**



Digital Weight Gauge



Different Length Tines



Special Build Options Available



TASK x NEXSYS **Battery Upgrade** 

**EMAIL:** SALES@TASKAUSTRALIA.COM.AU

WEB: TASKFORKLIFTS.COM.AU

CALL US: 1300 13 2002












1500 Kgs Capacity




Integrated Side-shift as Tilt Carriage Standard

### **TECHNICAL INFO**

|                                          | TWO STAGE                          |      |      |      | THREE STAGE |
|------------------------------------------|------------------------------------|------|------|------|-------------|
| Lift height metres                       | 2.5                                | 3.0  | 3.5  | 4.0  | 4.5 Tri     |
| A. Rated capacity at 600mm I.C. Kg       | 1500                               | 1500 | 1500 | 1500 | 1000        |
| B. Lift height mm                        | 2500                               | 3000 | 3500 | 4000 | 4500        |
| C. Extended height mm with load backrest | 3660                               | 4160 | 4660 | 5160 | 5660        |
| D. Collapsed height mm                   | 1770                               | 2020 | 2270 | 2520 | 2040        |
| E. Free lift mm                          | 350                                |      |      |      | 1435        |
| F. Chassis length mm to face of forks    | 770                                |      |      |      | 930         |
| G. Chassis width mm                      | 820                                |      |      |      |             |
| H. Wheelbase mm                          | 1342                               |      |      |      | 1538        |
| I. Carriage width mm                     | 815                                |      |      |      |             |
| J. Chassis under clearance mm            | 50                                 |      |      |      |             |
| K. Turning radius mm                     | 1722                               |      |      |      |             |
| L. Straddle I.D/ O.D mm.                 | 1220/1370 Or 1270/1420             |      |      |      |             |
| M. Weight less battery kg                | 740                                | 760  | 780  | 800  | 1355        |
| N. Battery compartment size mm           | 795mm x 188mm x 570mm high         |      |      |      |             |
| O. Right angle stacking aisle mm         | Dimension F + Load length + 100 mm |      |      |      |             |





STRADDLE **STACKER** 

Due to continuous product improvement, specifications are subject to change without notice or obligation. Some systems and features shown are optional at extra cost.